

Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: odorX ® Bad Odor Block Vanilla
Product code: LG-F1019
Recommended Use: Deodorizer

Supplier Bennett Direct Pty Ltd ABN: 93 413 737 810
Address: 23-27 Sheperd St, MARRICKVILLE NSW 2204
Tel: 1300 310 410 FAX: +61 2 9572 6565

Emergency telephone number POISONS INFORMATION CENTRE AUSTRALIA TEL: 131 126
NEW ZEALAND TEL: 0800 764 766

2. Hazards Identification

2.1 Classification of the substance or mixture

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

Classification according to GHS Regulation (EC) No 1272/2008

Flammable Liquids, Category 4	H227: Combustible liquid
Skin Corrosion/Irritation, Category 2	H315: Causes skin irritation
Sensitization, Skin, Category 1B	H317: May cause an allergic skin reaction
Eye Damage/Eye Irritation, Category 2A	H319: Causes serious eye irritation
Acute Toxicity Inhalation, Category 5	H333: May be harmful if inhaled
Aquatic Chronic Toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects

Classification OSHA (Provisions 1910.1200 of title 29)

Flammability Class IIIA	Combustible Liquid
Acute Dermal/Eye 12 :	Causes moderate skin irritation.
15 :	May cause eye irritation.
9 :	Harmful if absorbed through the skin.
Acute Oral 2 :	Harmful if swallowed
Sensitization/Allergic Response 31 :	May cause allergic skin reaction.
Target Organ Effects 26 :	Prolonged or repeated ingestion may cause damage to: kidneys, liver, spleen, blood, bile duct.

Carcinogenicity This mixture contains ingredients identified as carcinogens, at 0.1% or greater, by the following:
None [X] ACGIH [] IARC [] NTP [] OSHA []

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

2.2 Label elements

Hazard pictograms



Signal Word: Warning

Hazard statements

H227 Combustible liquid
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H333 May be harmful if inhaled
H411 Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention:

P235 Keep cool
P264 Wash hands thoroughly after handling
P272 Contaminated work clothing should not be allowed out of the workplace
P273 Avoid release to the environment

Response:

P302 + P352 IF ON SKIN: Wash with soap and water
 P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses if present and easy to do. continue rinsing
 P333 + P313 If skin irritation or a rash occurs: Get medical advice/attention
 P337 + P313 If eye irritation persists: Get medical advice/attention
 P362 Take off contaminated clothing and wash before reuse
 P363 Wash contaminated clothing before reuse
 P370 + P378 In case of fire: Use Carbon dioxide (CO2), Dry chemical, or Foam for extinction. Do not use a direct water jet on burning material
 P391 Collect Spillage

2.3 Other Hazards
 no data available

3. Composition/Information on Ingredients

3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

Liquid components embedded in wood fiber substrate.

CAS# Ingredient	EC#	Conc. Range	GHS Classification	OSHA Classification
104-21-2 <i>p-Anisyl acetate</i>	203-185-8	5 - 10 %	H303; H315; H319	12, 15
121-32-4 <i>Ethyl vanillin</i>	204-464-7	5 - 10 %	H303; H320; H402	
68647-72-3 <i>Citrus aurantium var. dulcis</i>	232-433-8	2 - 5 %	H226; H304; H315; H317; H400; H410	12, 3, 31
91-64-5 <i>Coumarin</i>	202-086-7	2 - 5 %	H302; H317; H402	12, 15, 2, 26, 31, 9
104-61-0 <i>gamma-Nonalactone</i>	203-219-1	2 - 5 %	H316	12, 15
121-33-5 <i>Vanillin</i>	204-465-2	1 - 2 %	H303; H319	31

See Section 16 for full text of GHS classification codes

Total Hydrocarbon Content (% w/w) = 4.65

4. First Aid Measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air and keep at rest. Obtain medical advice.

Eye Exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

Skin Exposure: Remove contaminated clothes. Wash thoroughly with water (and soap). Contact physician if symptoms persist.

Ingestion: Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: no data available

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Refer to Section 2.2 "Response"

5. Fire-Fighting measures

5.1 Extinguishing media

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable Do not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

During fire fighting: Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Not Applicable

7. Handling and Storage

7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid plastic and uncoated metal container. Keep air contact to a minimum.

7.3 Specific end uses

No information available

8. Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits: Contains no substances with occupational exposure limit values

Engineering Controls: Use local exhaust as needed.

8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc. as may be appropriate for the exposure

Respiratory protection: Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate.

Skin protection: Avoid Skin contact. Use chemically resistant gloves as needed.

9. Physical and Chemical Properties

Physical state Liquid impregnated fiber block	Odor and appearance Brown colored fiber block, odor: Vanilla	
Solubility in water insoluble	Vapor pressure (mm Hg) 0.0799	Vapor density (Air=1) not available
Evaporation (butyl acetate = 1) not available	Flash point 165 F (73.89 C)	VOC: 3%
Flammability limits in air, lower, % by volume 40 g/m3 for wood dust	Auto-ignition temperature 399.2 - 500 °F (204.4 - 260 °C) for wood	

10. Stability and Reactivity

10.1 Reactivity None

10.2 Chemical stability Stable

10.3 Possibility of hazardous reactions None known

10.4 Conditions to avoid None known

10.5 Incompatible materials Strong oxidizing agents, strong acids, and alkalis

10.6 Hazardous decomposition products None known

11. Toxicological Information

11.1 Toxicological Effects

Acute Toxicity Estimates (ATEs) based on the individual Ingredient Toxicity Data utilizing the "Additivity Formula"

Acute toxicity - Oral - (Rat) mg/kg (LD50: 5,128.21) Not classified - the classification criteria are not met

Acute toxicity - Dermal - (Rabbit) mg/kg (LD50: 5,181.35) Not classified - the classification criteria are not met

Acute toxicity - Inhalation - (Rat) mg/L/4hr (LC50: 23.20) May be harmful if inhaled

Skin corrosion / irritation Causes skin irritation

Serious eye damage / irritation Causes serious eye irritation

Respiratory sensitization Not classified - the classification criteria are not met

Skin sensitization May cause an allergic skin reaction

Germ cell mutagenicity Not classified - the classification criteria are not met

Carcinogenicity Not classified - the classification criteria are not met

Reproductive toxicity Not classified - the classification criteria are not met

Specific target organ toxicity - single exposure Not classified - the classification criteria are not met

Specific target organ toxicity - repeated exposure Not classified - the classification criteria are not met

Aspiration hazard Not classified - the classification criteria are not met

12. Ecological Information

12.1 Toxicity

Acute aquatic toxicity Not classified - the classification criteria are not met

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects

Toxicity Data on soil no data available
Toxicity on other organisms no data available
12.2 Persistence and degradability no data available
12.3 Bioaccumulative potential no data available
12.4 Mobility in soil no data available
12.5 Other adverse effects no data available

13. Disposal Considerations

13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

<u>DOT</u>	Not regulated
<u>IMDG</u>	Not regulated
<u>IATA</u>	Not regulated

15. Regulatory Information

U.S. Federal Regulations:

TSCA (Toxic Substance Control Act): All components of the substance/mixture are listed or exempt
40 CFR(EPCRA, SARA, CERCLA and CAA) This product contains NO components of concern.

U.S. State Regulations:

California Proposition 65 Warning No Warning required

Canadian Regulations:

DSL / NDSL 100.00% of the components are listed or exempt.

16. Other Information

GHS H-Statements referred to under section 3

Total Fractional Values

Total Fractional Values

(TFV) Risk	(TFV) Risk
(1.11) Skin Corrosion/Irritation, Category 2	(2.50) Sensitization, Skin, Category 1B
(1.79) Eye Damage/Eye Irritation, Category 2A	(1.88) Aquatic Chronic Toxicity, Category 2

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Material Safety Data Sheet