

## **NITRO 600**

Manufacturing Air Purification Equipment Since 1988

The NITRO 600, portable air filtration machine with impact resistant polyethylene housing and performance you have learned to expect of OmniAire equipment. The NITRO 600 is UL/CSA listed for your safety and to meet your high expectations and many project requirements.

## OmniAire 600N 230

Airflow Ratings with HEPA (cfm)200 to 600
Motorized Impeller (free flow)1000 cfm
Operating SpeedVariable
Power Requirements (Volts/Hz) * 230V/50-60Hz
Motor operating amps1.1 amp
Circuit breaker10 amp
Filtration Stages 3 to 4
HEPA Filter 99.97%@0.3 micron Tested/Certified
Net Weight With Filters16kg
Dimensions (LxWxH)63cmx47cmx47cm
Cabinetry Flame retardant polyethylene
Exhaust and Inlet Collars Diameter 10"
Carrying Handle Soft Rubber Grip1
Operational sound level (at 1 metre)58 to 68 dBA

\*230 Vac/50Hz operation has up to 20% less performance than 60Hz.

Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.





3067108

CONFORMS TO UL STD 507 CERTIFIED TO CAN/ CSA STD C22.2 NO. 113-M1984



Available in Australia from Bennett Direct Pty Ltd

Ph: 1300 310 410 www.bennettdirect.com.au

